


DISPOSITION OF THE FLANGES



N1-FILTER OUTLET N2-FILTER INLET

N1/N2 ACC. TO DIN2501 OR ASME B16.5 150lbs sq.in.
DRILLED ACC. TO PRESSURE CLASS

WITH BASKET-OR RING-ELEMENTS

RE ENTLÜFTUNG G1/4
AIR ESCAPE
DÉSAÉRATION

RS ENTLÉERUNG G1/2
DRAIN
VIDANGE

S SIEBAUSBAU
DISMOUNTING THE FILTER ELEMENT
DÉMONTAGE DU PANIER

*S=Q BEIMANTELSIEB
BY MULTI MANTLE ELEMENT
POUR LE PANIERS À MANTEAUX

GEHÄUSE GEGOSSEN
CASING CASTED
CORPS MOULÉ

ALLGEMEINTOLERANZEN DIN ISO2768-v
TOLERANCE DIN ISO2768-v
TOLÉRANCE DIN ISO2768-v

AUF WUNSCH, ON REQUEST, SUR DEMANDE

POS.1 DRUCKAUSGLEICH
EQUALIZATION OF PRESSURE
INDICATEUR DE DIFFÉRENCE DE PRESSION

POS.2 DIFFERENZDRUCKANZEIGER
DIFFERENCE PRESSURE INDICATOR
ÉQUILIBRAGE DE PRESSION

BESTELLBEISPIEL

ORDERING EXAMPLE
EXEMPLE DE COMMANDE

TYP	øG	Q	DN
2.05.5	340	750	150

øG	Q	DN N1/N2	PN/120°C	A	C	øD	E	F	J	L	M	O	R	*S	I	V	N	øZ	P	T	U	VOL. L	GEW. KG
265	500	100	10	160	745	230	400	240	75	890	570	395	830	650	40	265	220	14	770	20	65	2x35	235
	995				650		377	900						2x47								270	
	745	377			650		35	2x35						245									
	995	627			900		35	2x47						280									
340	500	150	10	190	778	290	360	295	90	1090	700	470	1020	680	55	330	290	18	970	25	65	2x50	350
	1020				610		920	55						2x65								420	
420	500	200	10	225	895	356	220	480	90	1385	920	550	1320	760	65	420	360	18	1260	25	80	2x96	585
	1110				435		1525	1055						585								1450	1010
	270	1155			387		525	1525		1055	585	1450	1010	68								1390	2x136
520	750	250	10	270	1215	434	432	525	95	1720	1160	585	1650	1010	68	520	460	23	1590	25	90	2x218	1110

SUBJECT TO ALTERATION

ÄNDERUNGEN VORBEHALTEN

MODIFICATIONS RÉSERVÉES

DUPLEX FILTER

DOPPELFILTER 2.05.5

FILTRE DOUBLE